



PART NUMBERING SYSTEM

1



SERIES TYPE
1 = Steel Case with Chrome Ring, Copper alloy Internals
2 = Stainless Steel Case, Copper alloy Internals
3 = Stainless Steel Case, 316 SS Internals
4 = Ammonia Gauge
5 = Copper alloy Case, Copper alloy Internals
6 = Forged Copper alloy Case, Copper alloy Internals
7 = Black Poly Case, Copper alloy Internals

SPECIAL FEATURES
0 = Standard Gauge
1 = Removable Ring, Adjustable Pointer

MOUNTING STYLE
1 = Lower Mount
2 = Center Back Mount
3 = Back Connection, U-clamp Panel Mount
4 = Back Connection, Front Flange, Panel Mount
5 = Bottom Connection, Back Flange, Wall Mount
9 = Back Connection, Back Flange

CASE FILLING
D = Dry
L = Glycerin Filled
S = Silicone Filled
T = Low Temp Glycerin/Water ¹ (86/14)
W = Ultra Low Temp Glycerin/Water ¹

(1) Special Request Only: See "Liquid Filling Sealed Gauges" page for details

CONNECTION
8 = 1/8" NPT Male
4 = 1/4" NPT Male
2 = 1/2" NPT Male

DIAL SIZE
10 = 1" Diameter
15 = 1 1/2" Diameter
20 = 2" Diameter
25 = 2 1/2" Diameter
35 = 3 1/2" Diameter
40 = 4" Diameter
45 = 4 1/2" Diameter
60 = 6" Diameter
85 = 8 1/2" Diameter

RANGE
A = 30/0" Hg Vac
CB = 30" Hg Vac/0/15 psi
CC = 30" Hg Vac/0/30 psi
CD = 30" Hg Vac/0/60 psi
CE = 30" Hg Vac/0/100 psi
CF = 30" Hg Vac/0/150 psi
CG = 30" Hg Vac/0/200 psi
CH = 30" Hg Vac/0/300 psi
B = 0/15 psi
C = 0/30 psi
D = 0/60 psi
E = 0/100 psi
F = 0/160 psi
G = 0/200 psi
H = 0/300 psi
I = 0/400 psi
J = 0/500 psi
K = 0/600 psi
L = 0/800 psi
M = 0/1000 psi
N = 0/1500 psi
O = 0/2000 psi
P = 0/3000 psi
Q = 0/4000 psi
R = 0/5000 psi
S = 0/6000 psi
T = 0/7500 psi
U = 0/10,000 psi
V = 0/15,000 psi
W = 0/20,000 psi

EXAMPLE: "201L-254E"
2 = Stainless Steel Case, Copper alloy Internals
0 = Standard Gauge
1 = Lower Mount
L = Glycerin Filled
25 = 2 1/2" Diameter Dial Size
4 = 1/4" NPT male
E = 0/100 psi

NOTE: Not all part numbers or options are available from stock. Consult PIC Gauges for availability.